

PREMIER: BOYS AND GIRLS.



| | |
|-------------------|--|
| Uppers | Made of genuine cow/buffalo leathers. Thickness 1.2-1.4 mm. |
| Linings | Leather/cloth/non-woven non allergic materials as per choice.. |
| Fasteners | Laces/Velcro/Buckles as per choice. |
| Soles | Poly urethane directly injected soles. Density: 0.75 +/- 0.5g/cc. Hardness: 70 +/-10Sh.A. Flex: 150000 cycles. Resistance to cut growth; Not more than 300%. Lead: Not more than 2 ppm. Abrasion: 250 mm3(Max) |
| Eyelets | Black enamelled aluminium eyelets 4.0 mm with washers. |
| Threads | Synthetic 40/3 and 60/2 nylon/polyester threads. 3-4 stitches per centimetre. |
| Insole | Fabric of 0.8 mm +/- 0.2mm thick laminated with 2.5m+/-0.5mm spongy foam or EVA |
| Laces | Black colour nylon/polyester round 3.0mm+/-0.5mm nylon laces.Length 65cms +/- 2.0 cms. |
| Buckles | Steel buckles with rustproof coating. Width 12.00-18.00mm confirming to the strap width. |
| Stiffeners | Counters: 1.2mm thermoplastic sheet. Toe puffs:0.8MM Thermoplastic sheet. |
| Sizes | 7-9, 10-12, 13-2, 3-5, 6-8, 9-11. |
| Colours | Black or White |

CANVAS / SPORT SHOES



| | |
|-------------------|--|
| Uppers | Canvas laminated drill with 2mm EVA. Breaking strength: N/3cm. Warp; 65+/-5 kgs. Weft:47+/-5 Kgs. GSM:265. Thickness of bare fabric: 0.60mm. Thickness of canvas with EVA lamination: 2.00mm. |
| Linings | Fabric laminated drill with EVA. |
| Fasteners | Same as upper. |
| Soles | Poly urethane directly injected soles. Density:0.75 +/- 0.5g/cc. Hardness: 70 +/-10Sh.A. Flex: 150000 cycles. Resistance to cut growth; Not more than 300%. Lead: Not more than 2 ppm. Abrasion: 250mm3(Max) |
| Eyelets | Aluminium enamelled.. Collar dia: 10 mm. Wall thickness; 0.30-0.35mm. |
| Threads | Synthetic 40/3 and 60/2 nylon/polyester threads. 3-4 stitches per centimetre. |
| Insole | Cotton drill padded with 2.5 mm EVA. |
| Laces | White,round polyester laces withplastic tips at ends. Length: 50cms for sizes upto 2 and 60 mm for bigger sizes |
| Stiffeners | White strobel cloth of 1.30 mm thick. |
| Sizes | 7-9, 10-12, 13-2, 3-5, 6-8, 9-11. |

We can make school shoes in any other design and colour as per customers' choice.

SUPREME: BOYS AND GIRLS



| | |
|-------------------|--|
| Uppers | PVC coated on PC/PV fabric(Woven or non woven). Thickness 1.8mm +/-0.2 mm. |
| Linings | Non allergic, 2mm foam laminated non woven fabric. |
| Fasteners | Laces/Velcro/buckles as per choice. |
| Soles | Poly urethane directly injected soles. Density:0.75 +/- 0.5g/cc. Hardness: 70 +/-10Sh.A. Flex: 150000 cycles. Resistance to cut growth; Not more than 300%. Lead: Not more than 2 ppm. Abrasion: 250 mm3 (max) |
| Eyelets | Black enamelled aluminium eyelets 4.0mm dia with washers. |
| Threads | Synthetic 40/3 and 60/2 nylon/polyester threads. 3-4 stitches per centimetre. |
| Insole | Fabric of 0.8 mm +/- 0.2mm thick laminated with 2.5m+/-0.5mm spongy foam or EVA |
| Laces | Black colour nylon/polyester round 3.0mm+/-0.5mm nylon laces. Length 65cms +/- 2.0cms. |
| Buckles | Steel buckles with rustproof coating. Width 12.00-18.00mm confirming to the strap width. |
| Stiffeners | 1.4mm strobel material/1.0mm. thermoplastic sheet for counters. |
| Sizes | 7-9, 10-12, 13-2, 3-5, 6-8, 9-11. |
| Colours | Black or White |